

CABLES TORSADES RESEAU

| Section de l'âme mm ² | Diamètre extérieur de la torsade mm | Masse approximative Kg/Km | Résistance Linéique Ohm/Km | Intensité en régime permanent A | Résistance à la rupture de l'âme daN |
|----------------------------------|-------------------------------------|---------------------------|----------------------------|---------------------------------|--------------------------------------|
| 3 x 35+54,6 | 26 | 615 | 0,868 | 138 | 1660 |
| 3 x 35+54,6+1x16 | 27,3 | 690 | 0,868 | 138 | 1660 |
| 3 x 35+54,6+2x16 | 29 | 775 | 0,868 | 138 | 1660 |
| 3x50+54,6 | 26,5 | 804 | 0,641 | 168 | 1660 |
| 3x50+54,6++1x16 | 28,9 | 877 | 0,641 | 168 | 1660 |
| 3x50+54,6+x2x16 | 33,3 | 950 | 0,641 | 168 | 1660 |
| 3x70+54,6 | 32,3 | 940 | 0,443 | 213 | 1660 |
| 3x70+54,6++1x16 | 33,2 | 1015 | 0,443 | 213 | 1660 |
| 3x70+54,6+x2x16 | 34,5 | 1090 | 0,443 | 213 | 1660 |

